

SECURE DATA STORAGE AND RETRIEVAL WITH KEY MANAGEMENT
AND USER AUTHENTICATION

Related Applications

09642879-082400
The present application is related to United States Patent Application Serial No. _____, entitled "SECURE DATA STORAGE AND RETRIEVAL IN A CLIENT-SERVER ENVIRONMENT", Attorney Docket No. 5577-203, the disclosure of which is incorporated by reference as if set forth fully herein.

Field of the Invention

The present invention relates to data processing systems and more particularly to the security of stored digital data.

Background of the Invention

With an ever increasing awareness among the public as to the privacy of digitally stored data, much attention has been focused on mechanisms for providing secure files and/or file access. Such security may become ever more important as, for example, more and more information is stored in a "file server" format. For example, with the recent introduction of publicly

accessible "Internet hard disks" where files of many different, and often unrelated, users are stored on Internet accessible servers, the issue of file security may become even more important. As is evidenced by, for example, the systems identified below, many differing solutions have been proposed to the problem of file security.

One conventional file security system is described in Allen G. Konheim, *Cryptography, A Primer*, John Wiley & Sons, New York, 1981, pp. 348-363, which describes a file security system called the Information Protection System (IPS). In IPS, each user has a secret passphrase, which is hashed by the system to produce a file encryption key. The file encryption key is then used to encrypt/decrypt that user's files. The encrypted files for all users are stored in a common system database. Each enciphered file has a file header. The file header contains such information as the type of encipherment used, a time-date stamp, the version of IPS employed, cryptographic chaining information and a key verification field, but it contains no encrypted key field, since IPS uses only a 1-level key management system.

Additional security systems are described in United States Patent Nos. 4,238,854, 4,757,533, 5,150,407, 5,235,641, 5,495,533, 5,563,946, 5,699,428, 5,719,941, 5,751,841, 5,787,169, 5,841,871, 6,011,847 and 6,023,506.

Summary of the Invention

Embodiments of the present invention include methods, systems and computer program products which provide for controlling access to digital data in a file by encrypting the data with a first key, encrypting the first key with a second personal key

001280-082100 09642879

generated from a password/passphrase associated with the file and further encrypting the encrypted first key with a control key which is managed by the system. In certain embodiments, user authentication may also be provided by issuing a ticket which is utilized to create, access and administer the files in the system.

In particular embodiments, the file system may include a file server, a personal key server and a personal key client. The file server is configured to store an encrypted file and a file header corresponding to the digital data of the file and containing an encryption key encrypted with both a personal key of an owner of the file and a control key. The personal key server is configured to receive a header associated with a file, the file header containing an encryption key encrypted with a personal key and encrypt encrypted encryption key with a control key to provide the file header containing an encryption key encrypted with both a personal key and a control key. The personal key client is configured to generate the encryption key, encrypt the digital data of the file with the encryption key, generate the personal key from a password associated with the file, encrypt the encryption key with the personal key, incorporate the encrypted encryption key in a file header associated with the file and provide the file header with the encryption key encrypted with the personal key to the personal key server, receive the file header from the personal key server and provide the file header received from the personal key server to the file server.

In further embodiments of the present invention, an authentication server may also be provided. The authentication server may be configured to receive access requests from the personal key client, determine

007880 " 682100 09642879

if the access request is authorized and provide a ticket to the personal key client if the access request is authorized. In such embodiments, the personal key client may be further configured to request access from the authentication server, receive the ticket from the authentication server and provide the ticket along with the file header to the personal key server and along with the encrypted file and the file header to the file server. Furthermore, the personal key server may be further configured to receive the ticket from the personal key client, determine the validity of the ticket and reject requests from the personal key client if the ticket is invalid. Finally, the file server may be further configured to receive the ticket from the personal key client, determine the validity of the ticket and reject requests from the personal key client if the ticket is invalid.

In still further embodiments of the present invention, the file may be accessed by the personal key client receiving a request to access the file by the file owner. The personal key client requests the file and the associated file header from the file server, extracts the encryption key encrypted with the personal key and the control key from the file header and requests that the personal key server recover the encrypted encryption key from the file header. The recovered encrypted encryption key is received from the personal key server. The personal key client generates the personal key from the password, decrypts the recovered encrypted encryption key with the personal key to recover the encryption key and decrypts the encrypted digital data with the recovered encryption key. The file server provides the file and the associated file header to the personal key client in response to the request for the file and the associated

personal key client and stores the received file header.

5 The personal key server receives the request to recover the encrypted file encryption key and decrypts the file encryption key encrypted with the personal key and the control key to provide the recovered encrypted encryption key. The personal key server then provides the recovered encrypted encryption key to the personal key client. The personal key server also receives the request to update the file header to incorporate the new personal key encrypted encryption key, encrypts the new personal key encrypted encryption key with the control key, incorporates the encryption key encrypted with the new personal key and the control key in the file header to provide an updated file header and returns the updated file header to the personal key client.

10 In further embodiments, the personal key client may include in the request to update of the file header by the personal key server to incorporate an identification of a user requesting to update the file header. In such embodiments, the personal key server may compare the identification of the user requesting to update the file header with the list of users authorized to access the file and reject the request if the user requesting to update the file header is not identified in the list of users authorized to access the file as the owner of the file.

20 In additional embodiments of the present invention, access by a trusted third party may be provided by the personal key client encrypting the encryption key with a public key of a trusted third party and incorporating the encryption key encrypted with the public key of a trusted third party into the file header. Furthermore, the personal key client may

007380" 62824960

receive a request by the trusted third party to access the file and request access to the file by the trusted third party from the file server. The personal key client receives the encrypted file and the file header from the file server, extracts the encryption key encrypted with the public key of the trusted third party from the received file header, obtains the private key of the trusted third party, decrypts the extracted encryption key encrypted with the public key of the trusted third party to recover the encryption key and decrypts the encrypted file with the recovered encryption key. The file server receives the request for access to the file by the trusted third party and provides the encrypted file and the associated file header to the personal key client in response to receiving the request for access to the file by the trusted third party.

In yet further embodiments of the present invention, the public key of the trusted third party may be updated by the personal key client requesting the file header associated with the file from the file server, receiving the file header from the file server, extracting the encryption key encrypted with the personal key and the control key and requesting that the personal key server recover the encrypted encryption key. The personal key client receives the recovered encrypted encryption key from the personal key server, generates the personal key, decrypts the recovered encrypted encryption key with the personal key, obtains a new public key associated with the trusted third party to provide a new public key encrypted encryption key, incorporates the new public key encryption key in the file header and provides the file header to the file server. The personal key server receives the request to recover the encrypted

file encryption key, decrypts the file encryption key encrypted with the personal key and the control key to provide the recovered encrypted encryption key and provides the recovered encrypted encryption key to the personal key client.

In yet further embodiments of the present invention, additional users may be given access to the file by the personal key client incorporating the encryption key unencrypted in the file header and providing the personal key server with a list of users authorized to have access to the file. The personal key server encrypts the unencrypted encryption key with the control key, incorporates the unencrypted encryption key encrypted with the control key in the file header and returns the file header incorporating the encryption key encrypted with the control key to the personal key client.

In such embodiments, the personal key client may be further configured to receive a request to access the file by a user other than the file owner, request the file and the associated file header from the file server, extract the encryption key encrypted with only the control key from the file header, request that the personal key server recover the encryption key from the file header, receive the recovered encryption key from the personal key server and decrypt the encrypted digital data with the recovered encryption key. The file server may be configured to provide the file and the associated file header in to the personal key client in response to the request for the file and the associated file header. The personal key server may be configured to receive a request from the personal key client to recover the encryption key in response to a request by a user other than the owner, the request from the personal key client containing the encryption

09642879 "082100
001280" 6784960

5 the file header. The personal key server compares the identification of the user requesting to update the file header with the list of users authorized to access the file and rejects the request if the user requesting to update the file header is not identified in the list of users authorized to access the file as the owner of the file.

10 In still further embodiments the other users may access the file by the personal key client receiveing a request from a user other than the owner to access the file. The personal key client requests the file and the associated file header from the file server, extracts the public key encrypted encryption key encrypted with the control key corresponding to the user requesting access to the file from the file header, requests that the personal key server recover the public key encrypted encryption key corresponding to the user requesting access to the file from the file header, receives the recovered public key encrypted encryption key from the personal key server. The personal key client obtains a private key associated with the user requesting access to the file, decrypts the recovered encrypted encryption key with the private key to recover the encryption key and decrypts the encrypted digital data with the recovered encryption key.

25 The personal key server receives a request from the personal key client to recover the public key encrypted encryption key containing the public key encrypted encryption key encrypted with the control key corresponding to the user requesting access to the file, decrypts the public key encrypted encryption key encrypted the control key with the control key and returns the public key encrypted encryption key

corresponding to the user requesting the file to the personal key client.

In still further embodiments of the present invention, the personal key client is further includes in the request to recover the public key encrypted encryption key corresponding to the user requesting to access the file an identification of the user requesting to access the file. The personal key server compares the identification of the user requesting to access the file with the list of users authorized to access the file and rejects the request if the user requesting to access the file is not identified in the list of users authorized to access the file.

While the invention has been described above primarily with respect to the system aspects of the invention, both methods and/or computer program products are also provided. Furthermore, additional embodiments of the present invention may include, for example, personal key servers and personal key clients.

Brief Description of the Drawings

Figure 1 is a block diagram of a system for encrypted file access according to embodiments of the present invention;

Figure 2 is a block diagram of data processing systems according to embodiments of the present invention;

Figure 3 is a more detailed block diagram of data processing systems according to embodiments of the present invention;

Figure 4 is a block diagram of a file and file header according to embodiments of the present invention;

09642879-082100

Figure 5 is a flowchart illustrating operations of a client of an owner of a file for creating or updating an encrypted file according to embodiments of the present invention;

5 **Figure 6** is a flowchart illustrating operations of an authentication server according to embodiments of the present invention;

10 **Figure 7** is a flowchart illustrating operations of a personal key server for creating a file header according to embodiments of the present invention;

Figure 8 is a flowchart illustrating operations of a file server for creating or updating an encrypted file according to embodiments of the present invention;

15 **Figure 9** is a flowchart illustrating operations of a client of an owner of a file for retrieving an encrypted file according to embodiments of the present invention;

20 **Figure 10** is a flowchart illustrating operations of a file server for retrieving an encrypted file according to embodiments of the present invention;

Figure 11 is a flowchart illustrating operations of a key server in response to a request to recover an encryption key according to embodiments of the present invention;

25 **Figure 12** is a flowchart illustrating operations of a client of a user associated with a file for retrieving an encrypted file according to embodiments of the present invention;

30 **Figure 13** is a flowchart illustrating operations of a client of a trusted third party associated with a file for retrieving an encrypted file according to embodiments of the present invention;

Figure 14 is a flowchart illustrating operations of a file server in response to a request to retrieve a

09642879-082100

file by a trusted third party associated with a file according to embodiments of the present invention;

Figure 15 is a flowchart illustrating operations of a client of an owner of a file for changing a password or passphrase associated with an encrypted file according to embodiments of the present invention;

Figure 16 is a flowchart illustrating operations of a file server in response to a request to access a file header associated with an encrypted file according to embodiments of the present invention;

Figure 17 is a flowchart illustrating operations of a key server in response to a request to update a file header associated with an encrypted file according to embodiments of the present invention;

Figure 18 is a flowchart illustrating operations of a client of an owner of a file for changing a public key of a trusted third party associated with an encrypted file according to embodiments of the present invention; and

Figure 19 is a flowchart illustrating operations of a client of an owner of a file for changing a public key of a user(s) associated with an encrypted file according to embodiments of the present invention.

Detailed Description of Preferred Embodiments

The present invention now will be described more fully hereinafter with reference to the accompanying drawings, in which preferred embodiments of the invention are shown. This invention may, however, be embodied in many different forms and should not be construed as limited to the embodiments set forth herein; rather, these embodiments are provided so that this disclosure will be thorough and complete, and will

fully convey the scope of the invention to those skilled in the art.

As will be appreciated by one of skill in the art, the present invention may be embodied as a method, data
5 processing system, or computer program product.

Accordingly, the present invention may take the form of an entirely hardware embodiment, an entirely software embodiment or an embodiment combining software and hardware aspects. Furthermore, the present invention
10 may take the form of a computer program product on a computer-usable storage medium having computer-usable program code means embodied in the medium. Any suitable computer readable medium may be utilized including hard disks, CD-ROMs, optical storage devices, a transmission media such as those supporting the Internet or an
15 intranet, or magnetic storage devices.

Computer program code for carrying out operations of the present invention may be written in an object oriented programming language such as Java®, Smalltalk
20 or C++. However, the computer program code for carrying out operations of the present invention may also be written in conventional procedural programming languages, such as the "C" programming language. The program code may execute entirely on the user's
25 computer, partly on the user's computer, as a stand-alone software package, partly on the user's computer and partly on a remote computer or entirely on the remote computer. In the latter scenario, the remote computer may be connected to the user's computer
30 through a local area network (LAN) or a wide area network (WAN), or the connection may be made to an external computer (for example, through the Internet using an Internet Service Provider).

The present invention is described below with
35 reference to flowchart illustrations and/or block

09642879-082100

diagrams of methods, apparatus (systems) and computer
program products according to embodiments of the
invention. It will be understood that each block of the
flowchart illustrations and/or block diagrams, and
combinations of blocks in the flowchart illustrations
and/or block diagrams, can be implemented by computer
program instructions. These computer program
instructions may be provided to a processor of a
general purpose computer, special purpose computer, or
other programmable data processing apparatus to produce
a machine, such that the instructions, which execute
via the processor of the computer or other programmable
data processing apparatus, create means for
implementing the functions specified in the flowchart
and/or block diagram block or blocks.

These computer program instructions may also be
stored in a computer-readable memory that can direct a
computer or other programmable data processing
apparatus to function in a particular manner, such that
the instructions stored in the computer-readable memory
produce an article of manufacture including instruction
means which implement the function specified in the
flowchart and/or block diagram block or blocks.

The computer program instructions may also be
loaded onto a computer or other programmable data
processing apparatus to cause a series of operational
steps to be performed on the computer or other
programmable apparatus to produce a computer
implemented process such that the instructions which
execute on the computer or other programmable apparatus
provide steps for implementing the functions specified
in the flowchart and/or block diagram block or blocks.

As is described in more detail below, the present
invention may provide for secure access to an encrypted
file utilizing two-level encryption where a file is

007280" 6284950

encrypted with a first key and where that key is encrypted with a second key generated from a password or passphrase associated with the file. As used herein, the terms password and passphrase are used interchangeably to refer to a value or sequence of values which may be provided by a user. The encrypted key may be further encrypted with a control key which may be managed by a key server to further control access to the file. The encrypted key may be stored in a header associated with the file and maintained on a server for access by a user. Additional embodiments of the present invention provide for storing, updating, retrieving and managing keys associated with users which have access to the file. Various embodiments of the present invention will now be described with reference to **Figures 1** through **19**.

Referring now to **Figure 1**, a system for secure access to encrypted data according to embodiments of the present invention is illustrated. As seen in **Figure 1**, a file server **102**, which may store encrypted files and encrypted headers associated with the files, has access to a network **104**. Similarly, an authentication server **100** and a personal key server **108** may also have access to the network **104**. The network **104** may be an intranet, an extranet, a virtual private network, the Internet, a wireless network, a direct dial connection or even a "sneaker" network where information is transmitted from processing system to processing system utilizing a removable storage media. Whatever the method of communication, the network **104** serves to provide communication between the authentication server **100**, the file server **102**, the personal key server **108** and client data processing systems **106** and **106'** which may access the encrypted

files and headers on the file server 102. As used herein, the terms client data processing system and client may be used interchangeably.

While systems according to embodiments of the present invention are illustrated as having a separate authentication server 100, file server 102, personal key server 108 and client data processing systems 106 and 106', as will be appreciated by those of skill in the art, such functions may be integrated into a single data processing system or may be distributed across multiple data processing systems. Furthermore, multiple authentication servers 100, file servers 102 and/or personal key servers 108 may be accessed by a single or multiple client data processing systems 106 and 106'. Additionally, while not illustrated in Figure 1, multiple data processing systems may access one or more of the authentication server(2) 100, the file server(s) 102, and/or the personal key server(s) 108 through one or more client data processing systems 106 and 106'. Thus, the client data processing systems 106 and 106' may act as servers and provide files to other data processing systems. Such a system may be beneficial where the authentication server 100, the file server 102 and/or the personal key server 108 communicate with the client data processing systems 106 and 106' over an insecure network but where the other data processing systems may communicate with the client data processing systems 106 and 106' over a secure network, through a direct connection or through other such trusted communication media. In such a system, the client data processing systems 106 and 106' may act as a gateway between the trusted communication media and the insecure network. Thus, the present invention

should not be construed as limited to the particular configuration illustrated in **Figure 1** but may be utilized with any configuration suitable for carrying out the operations described herein.

5 Referring now to **Figure 2**, an exemplary embodiment of a data processing system 230 suitable for use as either an authentication server 100, a file server 102, a personal key server 108 or a client data processing system 106 and/or 106' in accordance with embodiments
10 of the present invention is illustrated and may include input device(s) 232 such as a keyboard or keypad, a display 234, and a memory 236 that communicate with a processor 238. The data processing system 230 may further include a storage system 242, a speaker 244 and
15 an I/O data port(s) 246 that also communicate with the processor 238. The storage system 242 may include removable and/or fixed media such as floppy disks, ZIP drives, hard disks or the like as well as virtual storage such as a RAMDISK. The I/O data port 246 can
20 be used to transfer information between the data processing system 230 and another computer system or a network (e.g., the Internet). Such data processing systems may include, for example, personal computers, laptop computers, mainframe computers, pervasive
25 computing devices such as personal digital assistants, smartphones or the like, or even embedded processing systems. The components of a particular data processing system may be conventional or custom components, such as those used in many conventional
30 computing devices, which may be configured to operate as described herein.

Figure 3 is a block diagram of data processing systems that illustrate systems, methods, and computer program products in accordance with embodiments of the

represents the static and dynamic data used by the application program(s) 10, operating system 252, I/O device drivers 258, and other software programs that may reside in the memory 236.

5 As is further seen in **Figure 3**, for client processing systems, the application program(s) 10 preferably includes a personal key client 12. The personal key client 12 may function as described herein for providing access to encrypted files. For server
10 data processing systems, the application program 10 may, instead, include one or more of an authentication server module, a file server module or a personal key server module (not shown) which may store and control access to encrypted files and encrypted file headers as
15 described herein.

While the present invention is illustrated, for example, with reference to a personal key client 12 and an authentication server, a file server and a personal key server which carry out the operations for software
20 installation, as will be appreciated by those of skill in the art, the functions carried out by these modules may also be incorporated into for example, the operating system 252. Thus, the present invention should not be construed as limited to the configuration
25 of **Figure 3** but is intended to encompass any configuration capable of carrying out the operations described herein.

As briefly described above, in embodiments of the present invention, an encrypted file and an encrypted
30 file header are associated with each other. **Figure 4** illustrates such an arrangement. As seen in **Figure 4**, an encrypted file 400 may be a file which was encrypted with an encryption key ke and is illustrated in **Figure 4** as $ENC_{ke}(\text{file})$. An encrypted file header 402 is also

provided. The file header 402 may contain both encrypted and unencrypted portions. As illustrated in **Figure 4**, the file header may contain the tuple (*id*, *fid*) 404 where *id* is a user identification of an owner of the file and *fid* is a file identification associated with the file.

A file encryption key is stored in the file header
402 encrypted under a personal key k belonging to the
user, derived from a user-supplied

"passphrase/password." Such an encrypted file encryption key 406 is illustrated as $Enc_{ck}(Enc_k(ke, ki, hash(ke, ki)))$ in **Figure 4**. The file encryption key may also be encrypted with a public key or keys pk of one or more trusted third parties and incorporated in the file header 402 so as to allow third parties access to the file contents. Such an encrypted file encryption key 410 is illustrated as $Enc_{ck}(Enc_{pk}(ke, ki, hash(ke, ki)))$ in **Figure 4**. A message authentication code (MAC) 408 may also be included within the file header 402 to verify the authenticity of the file after decryption. Furthermore, the file encryption key may also be stored in the file header 402 encrypted under a public key pk belonging to a trusted third party. Such an encrypted file encryption key 410 is illustrated as $Enc_{pk}(ke, ki, hash(ke, ki))$ in **Figure 4**. Note that the file encryption key is not encrypted with the control key. Finally, one or more copies of the file encryption key may be stored in the file header 402 encrypted under a public key $pk1$ through pkn belonging to a user with access to the encrypted file. Such an encrypted file encryption key 412 is illustrated as $Enc_{ck}(Enc_{pk1}(ke, ki, hash(ke, ki)))$ in **Figure 4**.

$Enc_{pk}(ke, ki, hash(ke, ki))$ in **Figure 4**. Note that the file encryption key is not encrypted with the control key. Finally, one or more copies of the file encryption key may be stored in the file header **402** encrypted under a public key $pk1$ through pkn belonging to a user with access to the encrypted file. Such an encrypted file encryption key **412** is illustrated as $Enc_{ck}(Enc_{pk1}(ke, ki, hash(ke, ki)))$ in **Figure 4**.

encryption key may be stored in the file header **402** encrypted under a public key pk_1 through pkn belonging to a user with access to the encrypted file. Such an encrypted file encryption key **412** is illustrated as $Enc_{ck}(Enc_{pk_1}(ke, ki, \text{hash}(ke, ki)))$ in **Figure 4**.

As illustrated in **Figure 4**, the file encryption key may be stored in the file header encrypted under two keys: a personal key belonging to the user and a system key, called a control key, which is generated, managed, and controlled by the personal key server 108. In this case, both parties - the user and the personal key server 108 -- authorize access to an encrypted file. The personal key server 108 may require the personal key client to present it with a valid ticket issued to the personal key client by the authentication server 100. That is, the user must first be authenticated to the authentication server 100. Only then, will the personal key server 108 use its control key to decrypt the file encryption key. Since the file encryption key has been doubly encrypted, first with the personal key derived from the user's "passphrase" and second with the control key, the decrypted value returned by the personal key server 108 to the personal key client is the file encryption key encrypted with the personal key of the user. Hence, the key management solution is such that a file encryption key can be recovered in the clear, thus, enabling the encrypted file be decrypted, if the user desires to recover the file and the user has been authenticated to the system by the authentication server.

The personal key server 108 maintains an access control list (ACL) in its database to allow access to the file by potentially many system users. The access control list prescribes the rights of access to each file by each system user. If the user requesting access is in the access control list, the personal key server 108 will decrypt the encrypted file key under the control key and return same to the personal key client of the requesting user.

In various embodiments of the present invention, different options for key management may be provided when access to an encrypted file by a user, other than the *file owner*, is desired or required. The user who initially creates an encrypted file is also called the *file owner*. When access to an encrypted file by a user, other than the *file owner*, is desired or required, the file encryption key could be encrypted under a public key of the other user, in lieu of encrypting it with a personal key of that other user. Such an encryption is illustrated in Figure 4 as the encrypted key **412**. A second option would be to omit encrypting the file encryption key under a key belonging to the other user, and allow the personal key server to encrypt the key under its control key. That is, the file encryption key could be singly encrypted under the control key instead of doubly encrypted under a key belonging to the other user and the control key. In the second option, the encrypted key **412** would be $Enc_{ck}(ke, ki, \text{hash}(ke, ki))$ in **Figure 4**.

The personal key client provides the file server **102** with a ticket to prove its identity and for the file server **104** to enforce rules such as only allowing valid users to store files in the file server's database, or only the *file owner* of an existing file being allowed to replace the encrypted file or file header with an updated copy of the encrypted file or file header.

Embodiments of the present invention may provide enhancements to systems with fewer components such as that described in detail in commonly assigned and concurrently filed United States Patent Application Serial No. _____, entitled "SECURE DATA STORAGE AND RETRIEVAL IN A CLIENT SERVER ENVIRONMENT", Attorney

09642879 "082100
001280" 6324960

Docket No. 5577-203, the disclosure of which is incorporated by reference as if set forth fully herein.

For access to the resources at the file server 102, the user may have a unique "userid" denoted by *id*.
5 There can be any number of users but each user should have a unique userid (*i.e.*, ID) with regard to the file encryption system. Each file that the user wants to store on the file server has a "fileid" denoted by *fid*.
10 The fileids generated for a given userid should be unique with regard to a particular file system. The fileid may, for example, be generated from a file name provided by a user. However, fileids need not be unique across all users. Thus, the tuple (*id*, *fid*) uniquely identifies a single file on the file server 102 even
15 though there might be many files on the file server 102 with the same *fid*. All the files on the file server belonging to a given userid (*i.e.*, *id*) may be identified by the tuple (*id*, *). Similarly, less than all of the files could be identified for a user with various wildcard values for the fileid. A file may
20 contain any form of digital data such as video, audio, text, etc.

The file server 102 may honor all requests for access to encrypted files. Thus, a user who requests a
25 file from the file server 102, corresponding to tuple (*id*, *fid*) will be given the requested file if it exists and can be located. Thus, the file server 102 will typically not "screen" requests for files. Access to the unencrypted file is controlled via the file
30 encryption key management system (*i.e.*, via the encryption keys). However, the file server 102 does control requests to store encrypted files in the file server's database. Otherwise, an adversary could issue a request to the file server to store a file under a

key change operations. Thus, for example, to change which users are trusted third parties, the public key operations described below could be utilized to replace one third parties public key with anothers and, thereby, provide access to file to a different third party. Similarly, file ownership could be changed by allowing the new owner third party access to the file, the new owner could retrieve the file and store the file under a new tuple (*id*, *fid*) and, thereby, obtain ownership of the file. Thus, the core functions described herein may provide a robust feature set which may be readily expanded through combinations of operations. Furthermore, additional "file management" functions could also be incorporated, for example, utilizing conventional file server operations.

Data storage operations according to embodiments of the present invention will now be described with reference to **Figures 5** through **8**. **Figure 5** illustrates operations of a personal key client for data storage. **Figure 6** illustrates operations of the authentication server for data storage. **Figure 7** illustrates operations of a personal key server for data storage. **Figure 8** illustrates operations of the file server for data storage.

As seen in **Figure 5**, when a user wants to encrypt a file and store the encrypted file on the file server, the user submits their userid (*id*) and password/passphrase (*pw*) associated with the file to the personal key client (block **500**). The personal key client sends *id* and the user's credentials to the authentication server (block **501**) to request authentication of the user as an authorized user. The credentials may include a representation of the value of *pw* associated with the file (e.g., a hash value

Optionally, a rejected request message may be sent to the personal key client. The personal key server encrypts the encrypted encryption value, such as $Enc_k(ke, ki, Hash(ke, ki))$, with its control key, kc , thereby producing the encrypted value $Enc_{kc}(Enc_k(ke, ki, Hash(ke, ki)))$ (block 554). If the personal key client requests that additional users be given access to the file (block 556), then additional processing to encrypt the additional user key values with the control key (block 558). According to certain embodiments of the present invention, the personal key server encrypts the received value $(ke, ki, Hash(ke, ki))$ under kc , thereby producing the encrypted value $Enc_{kc}(ke, ki, Hash(ke, ki))$. In other embodiments, the personal key server encrypts the several received values $Enc_{pk1}(ke, ki, Hash(ke, ki))$, $Enc_{pk2}(ke, ki, Hash(ke, ki))$, etc., under kc , thereby producing the encrypted values $Enc_{kc}(Enc_{pk1}(ke, ki, Hash(ke, ki)))$, $Enc_{kc}(Enc_{pk2}(ke, ki, Hash(ke, ki)))$, etc.

In any event, the personal key server creates a new entry in the database, which includes building an access control list of authorized users that are entitled to access the encrypted file (block 560). The personal key server also prepares a file header (block 562), which contains among other things the values (id , fid), $Enc_{kc}(Enc_k(ke, ki, Hash(ke, ki)))$, MAC , and $Enc_{pk}(ke, ki, Hash(ke, ki))$. If additional users are to be given access to the file, then additional information is incorporated into the file header.

Thus, according to certain embodiments, the encrypted value $\text{Enc}_{kc}(ke, ki, \text{Hash}(ke, ki))$ is also stored in the file header. In other embodiments, the several encrypted values $\text{Enc}_{kc}(\text{Enc}_{pk1}(ke, ki, \text{Hash}(ke, ki)))$, $\text{Enc}_{kc}(\text{Enc}_{pk2}(ke, ki, \text{Hash}(ke, ki)))$, etc., are also

stored in the file header. The file header is returned to the personal key client (block 564). Note that the encrypted value $Enc_{pk}(ke, ki, Hash(ke, ki))$ is not further encrypted with the control key kc .

5 Returning to **Figure 5**, the personal key client also encrypts the content of the file with ke using a symmetric-key encryption algorithm (such as DES, Triple-DES, RC5, etc) (block 518). That is, $Enc_{ke}(file)$. Again, the personal key client may choose to split the
10 file into pieces (e.g., $piece_1, piece_2, \dots$) and encrypt each piece individually. This may allow data recovery to be done in pieces which may be useful for audio or video applications when data streaming is used.

 The personal key client next associates the file
15 header with the encrypted file (block 520). The header associated with each file preferably accompanies the file in case the file is moved or renamed or backed-up. The header may be associated with the file in a number of ways. For example, the header may be stored as the
20 first few bytes of the file, as a trailer at the end of the file, in the file's directory entry, in a separate area associated with the file's directory entry, in a local database or combinations thereof.

 The personal key client determines if the storage
25 operation is an update or the creation of a new file (block 522) and sends a "store new encrypted file" request (block 526) or a "store updated encrypted file" request (block 524) to the file server that includes the encrypted file, $Enc_{ke}(file)$, the file header and the
30 ticket. A "store new encrypted file" request indicates that the encrypted file is a new file to be stored under the tuple (id, fid) , whereas a "store updated encrypted file" request indicates that the encrypted file is intended to replace an existing file currently

stored under the tuple (id, fid) . In either case, the personal key client waits for confirmation of the store request (block 528).

Turning now to **Figure 8**, the operations of the file server may begin when the file server receives either the "store new encrypted file" or the "store updated encrypted file" requests (block 600). The file server verifies the validity of the received ticket (block 601) and then verifies that the *id* in the received tuple (*id*, *fid*) matches the *userid* in the ticket (block 603). The latter check on *id* is performed to ensure that only valid users, and more particularly only the file owner, can store an encrypted file, either a new file or an updated file, in the file server database. If both checks succeed, the procedure continues. Otherwise, the received "store new encrypted file" request or "store updated encrypted file" request is rejected (block 614).

If a "store new encrypted file" request is received (block 602), the file server verifies that no directory entry exists for the tuple (*id*, *fid*) received in the "store new encrypted file" request (block 610). If no such directory entry exists, the file server creates a new file directory entry, it stores the file header in accordance with a predetermined one of the aforementioned techniques for associating the file header with the encrypted file, and it stores the received encrypted file in its database (block 612). Otherwise, the "store new encrypted file" request is rejected and a rejected response is sent to the client (block 614).

If a "store updated encrypted file" request is received (block 602), the file server verifies that a directory entry exists for the tuple (id, fid) received

001280" 6/824960

or file user. **Figure 12** illustrates operations of the personal key client for data retrieval by an authorized user. **Figure 13** illustrates operations for data retrieval by a trusted third party. **Figure 14** illustrates operations of the file server for data retrieval by a trusted third party. As seen in **Figures 9 through 14**, a file stored on a file server may be retrieved and recovered by a user with access rights such as the file owner, a trusted third party or other authorized users.

Turning to **Figure 9**, when a user wants to retrieve and decrypt a file stored on the file server, the user submits their *userid (id)* and password/passphrase (*pw*) to the personal key client (block 650). The personal key client sends *id* and the user's credentials to the authentication server (block 651) to request authentication of the user as an authorized user. As described above, the credentials may include a representation of the value of *pw* associated with the file (e.g., a hash value computed on *pw*) or a different password/passphrase (i.e., different from the value of *pw* specified block 650).

Operations of the authentication server in response to receiving a request for authentication are seen in **Figure 6**. As described above, the authentication server provides a ticket to the personal key client in response to the authentication request which is received by the personal key client (block 653).

The user also requests access to a named file (corresponding to a *fid*) stored on the file server (block 652) by, for example, either specifying a file name of a fileid. If a file name is specified, the personal key client maps the named file to a file ID

(*fid*) (block 654). In either case, the personal key client sends an "access encrypted file" request, along with the tuple (*id*, *fid*), to the file server (block 656). The personal key client then waits to receive the response to the request from the file server.

Turning to **Figure 10**, when the file server receives the request to access the encrypted file (block 682), the file server verifies the validity of the received ticket (block 684). If the ticket is not valid, the request is rejected and a rejected response may be provide to personal key client (block 685). The file server also verifies that a directory entry exists for the tuple (*id*, *fid*) received in the "access encrypted file" request (block 686). If so, the file server responds by sending the encrypted file, $Enc_{ke}(\text{file})$, and its associated file header to the personal key client (block 688). If a directory entry does not exist for the tuple (*id*, *fid*), then the file server sends a "negative" response message to the personal key client (block 685).

Returning to **Figure 9**, when the personal key client receives the response from the file server, if the response is negative, then operations of **Figure 9** may terminate at block 656 and, optionally, the error may be reported to the user. However, if the response provides the encrypted file and file header, the personal key client receives the encrypted file and file header (block 658) and sends a "recover file encryption key" request to the personal key server containing the ticket, the user *id* and the file header (block 659).

Turning to **Figure 11**, the operations of the personal key server are illustrated in responding to a recover file encryption key request. As seen in **Figure**

11, upon receiving the "recover file encryption key" request (block 730), the personal key server compares the user *id* (from the ticket) against the user *id* of the file owner and the *ids* of other users in its stored access control list (block 730). Based on this comparison, the personal key server may determine the relationship between the user requesting recovery of the encryption key and the encrypted file (e.g. owner, user or no relationship) (block 732). If the requestor's *id* is not found (block 732), then the personal key server rejects the access request (block 733). Optionally, a message may be returned informing the personal key client that the request was rejected. However, if the *id* is found, and it matches the *id* of the file owner, then the personal key server extracts the encrypted value $\text{Enc}_{kc}(\text{Enc}_k(\text{ke}, \text{ki}, \text{Hash}(\text{ke}, \text{ki})))$ from the file header (block 735), decrypts it with its control key *kc* (block 737), and sends the decrypted value $\text{Enc}_k(\text{ke}, \text{ki}, \text{Hash}(\text{ke}, \text{ki}))$ back to the personal key client (block 738). On the other hand, if the *id* is found, and it matches *id* of one of the other users to be given access to the file, other than the file owner, then the personal key server extracts the encrypted value $\text{Enc}_{kc}(\text{ke}, \text{ki}, \text{Hash}(\text{ke}, \text{ki}))$ or $\text{Enc}_{kc}(\text{Enc}_{pki}(\text{ke}, \text{ki}, \text{Hash}(\text{ke}, \text{ki})))$ depending on the particular embodiment from the file header (block 734), decrypts the extracted value (block 736) with its control key *kc*, and sends the decrypted value $(\text{ke}, \text{ki}, \text{Hash}(\text{ke}, \text{ki}))$ or $\text{Enc}_{pki}(\text{ke}, \text{ki}, \text{Hash}(\text{ke}, \text{ki}))$ back to the personal key client (block 738). A used herein, *pki* is the public key of the "other user."

Returning to **Figure 9**, the personal key client receives the recovered personal key encrypted file encryption key from the personal key server (block 661)

and generates a key encrypting key k (block 660). The key encrypting key k may be generated, for example, as follows:

$$k = \text{Hash}(id, pw, fid).$$

5 The personal key client decrypts the received value, such as $Enc_k(ke, ki, Hash(ke, ki))$, from the personal key server with k to recover the encrypted values (block 664), such as ke , ki and $Hash(ke, ki)$. That is, $ke, ki, Hash(ke, ki) = Dec_k(Enc_k(ke, ki, Hash(ke, ki)))$. The personal key client computes Hash(ke, ki) on the decrypted ke, ki (block 666) if Hash(ke, ki) is provided in the header and compares it with the decrypted value of Hash(ke, ki) to see if they are equal (block 668). If they are equal, then ke and ki are recovered correctly and they have not been changed. If the keys have been recovered correctly, the personal key client decrypts the encrypted file $Enc_{ke}(file)$ with ke (block 670). That is,

$$\text{file} = \text{Dec}_{k_e}(\text{Enc}_{k_e}(\text{file})).$$

20 If the hash values are not equal, then an error has
occurred and the error may be reported to the user
(block **680**). Operations would then terminate.

If a MAC is incorporated in the file header, then operations of blocks 672 through 676 may be performed.

25 The personal key client generates a MAC (message authentication code) on the decrypted content of the file with *ki* (block 672). For example, the MAC may be generated by determining,

$$\text{MAC} = \text{Hash}(\text{file}, k_i).$$

```

30      The personal key client checks to see if the MAC that
      it generated is equal to the MAC that it received in
      the file header from the file server (block 676).  If
      they are equal, then the file is recovered correctly
      and its content has not been changed and the contents

```


may be provided to the user (block 678). If the MAC values are not equal, then an error has occurred, the error may be reported to the user (block 680) and operations may terminate.

5 **Figure 12** illustrates the operations of the personal key client when an "other user" accesses the encrypted file. When an "other user" wants to retrieve and decrypt a file stored on the file server, the user submits their userid (*id*) and password/passphrase (*pw*)
10 to the personal key client (block 1650). The personal key client sends *id* and the user's credentials to the authentication server (block 1651) to request authentication of the user as an authorized user. As described above, the credentials may include a
15 representation of the value of *pw* associated with the file (e.g., a hash value computed on *pw*) or a different password/passphrase (i.e., different from the value of *pw* specified block 1650).

Operations of the authentication server in
20 response to receiving a request for authentication are seen in **Figure 6**. As described above, the authentication server provides a ticket to the personal key client in response to the authentication request which is received by the personal key client (block
25 1653).

The user also requests access to a named file (corresponding to a *fid*) stored on the file server (block 1652) by, for example, either specifying a file name of a fileid. If a file name is specified, the
30 personal key client maps the named file to a file ID (*fid*) (block 1654). In either case, the personal key client sends an "access encrypted file" request, along with the tuple (*id*, *fid*), to the file server (block

and compares it with the decrypted value of $\text{Hash}(ke, ki)$ to see if they are equal (block 1668). If they are equal, then ke and ki are recovered correctly and they have not been changed. If the keys have been recovered correctly, the personal key client decrypts the encrypted file $\text{Enc}_{ke}(\text{file})$ with ke (block 1670). That is,

$\text{file} = \text{Dec}_{ke}(\text{Enc}_{ke}(\text{file}))$.

If the hash values are not equal, then an error has occurred and the error may be reported to the user (block 1680). Operations would then terminate.

If a MAC is incorporated in the file header, then operations of blocks 1672 through 1676 may be performed. The personal key client generates a MAC (message authentication code) on the decrypted content of the file with ki (block 1672). For example, the MAC may be generated by determining,

$\text{MAC} = \text{Hash}(\text{file}, ki)$.

The personal key client checks to see if the MAC that it generated is equal to the MAC that it received in the file header from the file server (block 1676). If they are equal, then the file is recovered correctly and its content has not been changed and the contents may be provided to the user (block 1678). If the MAC values are not equal, then an error has occurred, the error may be reported to the user (block 1680) and operations may terminate.

Turning to **Figure 13**, operations for data retrieval by a trusted third party are illustrated. When the trusted third party wants to retrieve and recover a file (fid) associated with a $userid$ id , the trusted third party requests access to a named file (corresponding to a fid) stored on the file server belonging to the file owner whose $userid$ is id by

providing, for example, the name of the file to retrieve (block 700) and, possibly, the id of the owner of the file. The personal key client maps the named file to a file ID (*fid*) (block 702) and creates the tuple (*id*, *fid*). The userid utilized to create the tuple may be obtained from the trusted third party or may be stored by the personal key client or the file server. In any event, the personal key client sends an "access encrypted file for trusted third party" request, along with the tuple (*id*, *fid*), to the file server (block 704).

Operations of the file server in response to the "access encrypted file for trusted third party request" are illustrated in **Figure 14**. As seen in **Figure 14**, when the request for access encrypted file for trusted third party is received (block 690), the file server verifies that a directory entry exists for the tuple (*id*, *fid*) received in the "access encrypted file" request (block 692). If so, the file server responds by sending the encrypted file, $Enc_{ke}(\text{file})$, and its associated file header to the personal key client (block 696). If a directory entry does not exist for the tuple (*id*, *fid*), then the file server sends a "negative" response message to the personal key client (block 694). Note that in the instance where the request is for access by the trusted third party, no ticket is required and no validation of a ticket is performed by the file server. Alternatively, a ticket could be requested by the trusted third party and provided to the file server. In such a case, operations may be performed as described with reference to **Figure 10**.

When the personal key client receives the response from the file server, if the response is negative,

operations of **Figure 13** may terminate at block 704 and, optionally, the error may be reported to the user.

However, if the response provides the encrypted file and file header, the personal key client extracts the encrypted value associated with the trusted third party from the header (block 708), for example, $\text{Enc}_{pk}(ke, ki, \text{Hash}(ke, ki))$. The extracted encrypted value is decrypted with the trusted third party's private key sk to recover the encryption key utilized to encrypt the file (block 710). For example, in the embodiment illustrated in **Figure 13**, the values ke , ki and $\text{Hash}(ke, ki)$ may be recovered. That is, ke , ki , $\text{Hash}(ke, ki) = \text{Dec}_{sk}(\text{Enc}_{pk}(ke, ki, \text{Hash}(ke, ki)))$.

If a hash value is provided, the personal key client computes $\text{Hash}(ke, ki)$ on the decrypted ke , ki (block 712) and compares the result with the decrypted value of $\text{Hash}(ke, ki)$ to see if they are equal (block 714). If the hash values are equal, then ke and ki are recovered correctly and they have not been changed.

The personal key client may then decrypt the encrypted file $\text{Enc}_{ke}(\text{file})$ with ke (block 716). That is,

$$\text{file} = \text{Dec}_{ke}(\text{Enc}_{ke}(\text{file})).$$

If the hash values are not equal (block 714), then an error has occurred and this error may, optionally, be reported to the user (block 726) and operations may terminate.

If a MAC is provided in the file header, then the operations of blocks 718 through 722 of **Figure 13** may be performed. The personal key client generates a MAC (message authentication code) on the unencrypted content of the file with ki (block 718). That is,

$$\text{MAC} = \text{Hash}(\text{file}, ki).$$

The personal key client extracts the MAC from the file header (block 720) and determines if the MAC that it

generated is equal to the MAC that it received in the file header from the file server (block 722). If they are equal, then the file is recovered correctly and its content has not been changed. The contents are then provided to the user (block 724). If the MAC values are not equal (block 722), then an error has occurred and this error may, optionally, be reported to the user (block 726) and operations may terminate.

Figures 15 through 19 illustrate operations for changing a password or passphrase for a file and for changing the public key of a trusted third party or a user. **Figure 15** illustrates operations carried out by a personal key client to change a password for a file or files. **Figure 16** illustrates operations of a file server for changing the password/passphrase or the public key of a trusted third party or other user for a file or files. **Figure 17** illustrates operations of a personal key server in response to an "update file header" request. **Figure 18** illustrates operations of a personal key client for changing the public key of a trusted third party. **Figure 19** illustrates operations of a personal key client for changing the public key of an other user in embodiments where the encryption key is encrypted with a public key of an other user.

Turning to **Figure 15**, when the user wants to change their current (*i.e.*, old) password/passphrase *pw* to a "new password/passphrase" *new_pw*, the personal key client obtains the user's userid (*id*), current password/passphrase (*pw*), and new password/passphrase (*new_pw*) (block 750) by, for example, the user submitting it to the personal key client. The user may also request a password/passphrase change and may specify which file or files are to be changed. Such a specification may be provided by providing the file

name or names, fileid or fileids, by providing a wildcard, such as "*" or combination of wildcards, such as "?", and partial file name or fileids which may be utilized as a criteria for selecting the files for which password changes are to be applied. For example, if the wildcard "*" is specified, all files for a give user will have the password changed. Alternatively, because the key for a given file is based on the files password, the "*" designator could change the password for all files with the password *pw*.

The personal key client sends *id* and the user's credentials to the authentication server (block 751) to request authentication of the user as an authorized user. As described above, the credentials may include a representation of the value of *pw* associated with the file (e.g., a hash value computed on *pw*) or a different password/passphrase (i.e., different from the value of *pw* specified block 750).

Operations of the authentication server in response to receiving a request for authentication are seen in **Figure 6**. As described above, the authentication server provides a ticket to the personal key client in response to the authentication request which is received by the personal key client (block 753).

The personal key client sends an "access file headers" request along with the tuple defining the userid and the fileids, for example, (*id*, *), and the received ticket to the file server (block 752).

As illustrated in **Figure 16**, in response to the "access file headers" request (block 800), the file server verifies the ticket received from the personal key client (block 801) and, if the ticket is verified, responds by obtaining the file headers corresponding to

the provided tuple, for example, $(id, *)$ (block 802). The file server sends the obtained file headers to the personal key client (block 804) and the file server waits for a response from the personal key client (block 806). If the ticket does not verify, then the rejected response is sent to the client (block 814).

Returning to **Figure 15**, the personal key client receives the file header(s) from the file server (block 754) and sends a "recover file encryption key" request to the personal key server to recover the file encryption keys for the file headers (block 755) by providing the tuple, for example, $(id, *)$, and the ticket from the authentication server. This operation may be a "batch" operation where all encryption keys are recovered and then processed or it may be performed serially where a file encryption key is processed and then another obtained. Thus, in response to the request to recover file encryption keys the personal key server carries out the operations as illustrated in **Figure 11**. Accordingly, in response to the "recover file encryption keys" request, the personal key server compares the requestor's id (from the ticket) against the id of the file owner in its stored access control list. If the requestor's id is not found, then the personal key server rejects the access request. However, if the id is found, and it matches the id of the file owner, then the personal key server extracts an encrypted value $Enc_{kc}(Enc_k(ke, ki, Hash(ke, ki)))$ from each file header, decrypts it with its control key kc , and sends the decrypted values $Enc_k(ke, ki, Hash(ke, ki))$ back to the personal key client in the form of a tuple $(fid, Enc_k(ke, ki, Hash(ke, ki)))$. Providing the decrypted $Enc_k(ke, ki, Hash(ke, ki))$ values with the fid values thus allows the personal key client to correctly

associate each $\text{Enc}_k(ke, ki, \text{Hash}(ke, ki))$ value with its corresponding file header.

The personal key client receives the recovered keys (block 757) and obtains a recovered encrypted key for processing (block 756). The personal key client extracts the tuple (id, fid) from the file header (block 758) and generates the key encrypting key k (block 760). That is,

$$k = \text{Hash}(id, pw, fid).$$

The personal key client matches the fid and the encrypted value encrypted with k from the personal key server (block 762), for example, $\text{Enc}_k(ke, ki, \text{Hash}(ke, ki))$, and decrypts the encrypted value with k (block 762) to recover the encryption key(s), such as ke, ki and $\text{Hash}(ke, ki)$. That is, $ke, ki, \text{Hash}(ke, ki) = \text{Dec}_k(\text{Enc}_k(ke, ki, \text{Hash}(ke, ki)))$.

If a hash value is present in the encrypted value, the personal key client also computes $\text{Hash}(ke, ki)$ using the decrypted ke, ki (block 764) and compares the computed hash value with the decrypted $\text{Hash}(ke, ki)$ to determine if they are equal (block 766). If they are equal, then ke and ki are recovered correctly and they have not been changed. If they are not equal, then processing of the current header is concluded and, if more headers are available for processing (block 774), a next header is obtained (block 756) and processing begins again with block 758. Such an error may also generate a message to a user so as to indicate that the password of the file associated with the file header was not changed and/or that an error occurred processing the header file.

If the hash values are equal, the personal key client generates the new key encrypting key new_k (block 768). That is,

$new_k = \text{Hash}(id, new_pw, fid).$

The personal key client encrypts the key values, for example, ke , ki and $\text{Hash}(ke, ki)$, with new_k (block 770). That is,

5 $\text{Enc}_{new_k}(ke, ki, \text{Hash}(ke, ki)).$

The personal key client replaces the current value of the encrypted keys, such as $\text{Enc}_k(ke, ki, \text{Hash}(ke, ki))$, in the file header with the new value $\text{Enc}_{new_k}(ke, ki, \text{Hash}(ke, ki))$ (block 772). At this point, the personal key client may continue processing additional file headers if any remain (block 774).

10

If no more file headers remain (block 774), the personal key client sends an "update file header" request or requests to the personal key server (block 773) along with the updated file headers and the ticket.

15

Operations of the personal key server in response to the update file headers request are illustrated in **Figure 17**. When the personal key server receives the update the file headers (block 820), the personal key server verifies the ticket received with the request (block 822). If the ticket does not verify, the request is rejected and a rejected response may be sent to the client (block 824). If the ticket verifies (block 822), the personal key server compares the requestor's id (from the ticket) against the id of the file owner in its access control list (block 823). If the requestor's id is not found, then the personal key server rejects the access request (block 824).

25

However, if the id is found, and it matches the id of the file owner, then for each tuple $(fid, \text{Enc}_{k_new}(ke, ki, \text{Hash}(ke, ki)))$ the personal key server encrypts $\text{Enc}_{k_new}(ke, ki, \text{Hash}(ke, ki))$ with its control key kc to produce $\text{Enc}_{kc}(\text{Enc}_{k_new}(ke, ki, \text{Hash}(ke, ki)))$ (block 826)

30

rejection of an "update file headers" request may include a request to update a file header which does not exist or which has been "locked" by the file server.

5 In any event, when the personal key client receives the response from the file server, operations continue at block 780 of **Figure 15**. The personal key client removes all unneeded copies of the file headers from its memory. As with the systems described above, 10 if the file headers are maintained locally, this may involve removing the file headers from working memory. Thus, at block 780, the personal key client deletes all the information associated with this password/passphrase change operation from its 15 memory/storage (i.e., keys, password/passphrase, encrypted information).

001230 62824960

Figure 18 illustrates operations for changing the public key of a trusted third party. The user or personal key client may be informed when the trusted third party changes its public key. For example a server may send a new certificate, containing the new public key, to the user or personal key client. Alternatively, as noted above, these procedures may be utilized to change the third party which is trusted. Thus, for example, if an employee leaves a company, a new trusted third party could be designated by replacing the public key of the former employee with that of a new employee.

However the notification of a change in a public key occurs, the operations of **Figure 18** may be carried out when the public key of a trusted third party is to be changed from a current (*i.e.*, old) public key *pk* to a "new public key" *new_pk*. As seen in **Figure 18**, the personal key client obtains a userid (*id*), current password/passphrase (*pw*), fileid(s) and new public key *new_pk* (block 850). Such information may be obtained by the user providing some or all of the information to the personal key client and indicating that a public key update is to be performed. As described above, the files for which the public key update may be performed may be specified in any of the various ways described above.

The personal key client sends *id* and the user's credentials to the authentication server (block 851) to request authentication of the user as an authorized user. As described above, the credentials may include a representation of the value of *pw* associated with the file (*e.g.*, a hash value computed on *pw*) or a different password/passphrase (*i.e.*, different from the value of *pw* specified block 850).

the file owner, then the personal key server extracts an encrypted value $\text{Enc}_{k_c}(\text{Enc}_k(ke, ki, \text{Hash}(ke, ki)))$ from each file header, decrypts it with its control key k_c , and sends the decrypted values $\text{Enc}_k(ke, ki, \text{Hash}(ke, ki))$ back to the personal key client in the form of a tuple $(fid, \text{Enc}_k(ke, ki, \text{Hash}(ke, ki)))$. Providing the decrypted $\text{Enc}_k(ke, ki, \text{Hash}(ke, ki))$ values with the fid values thus allows the personal key client to correctly associate each $\text{Enc}_k(ke, ki, \text{Hash}(ke, ki))$ value with its corresponding file header.

The personal key client receives the recovered keys (block 857) and obtains a file header for processing (block 856). The personal key client extracts the tuple (id , fid) from the file header (block 858) and generates the key encrypting key k (block 860). That is,

$$k = \text{Hash}(id, pw, fid).$$

The personal key client also matches the *fid* with a value encrypted with *k* from the personal key server, for example, $\text{Enc}_k(\text{ke}, \text{ki}, \text{Hash}(\text{ke}, \text{ki}))$, and decrypts it with *k* to recover the encryption keys (block 862), for example, *ke*, *ki* and $\text{Hash}(\text{ke}, \text{ki})$. That is, *ke*, *ki*, $\text{Hash}(\text{ke}, \text{ki}) = \text{Dec}_k(\text{Enc}_k(\text{ke}, \text{ki}, \text{Hash}(\text{ke}, \text{ki})))$.

If a hash value is provided with the encrypted key(s), the personal key client computes Hash(ke , ki) using the decrypted ke , ki (block 864) and compares it with the decrypted Hash(ke , ki) to determine if they are equal (block 866). If they are equal, then ke and ki are recovered correctly and they have not been changed. If they are not equal, then processing of the current header is concluded and, if more headers are available for processing (block 872), a next header is obtained (block 856) and processing begins again with block 858. Such an error may also generate a message

to a user so as to indicate that the public key of the trusted third party was not changed and/or that an error occurred processing the header file.

If the hash values are equal, the personal key client encrypts the key values, such as ke , ki and $\text{Hash}(ke, ki)$, with new_pk (block 868). That is,

$$\text{Enc}_{new_pk}(ke, ki, \text{Hash}(ke, ki)).$$

The personal key client replaces the current value of the encrypted keys, such as $\text{Enc}_{pk}(ke, ki, \text{Hash}(ke, ki))$, in the file header with the new value of the encrypted keys, such as, $\text{Enc}_{new_pk}(ke, ki, \text{Hash}(ke, ki))$ (block 870). If there are more headers to process (block 872), then a next header is obtained (block 856) and processing continues at block 858.

If there are no more headers to process, the personal key client sends a "store updated file headers" request to the file server, along with the updated file headers (block 874). Operations of the file server are carried out as described above with reference to **Figure 16** and the personal key client waits for a response from the file server (block 876). When the personal key client receives the response from the file server, operations continue at block 878 of **Figure 18**. The personal key client removes all unneeded copies of the file headers from its memory. As with the systems described above, if the file headers are maintained locally, this may involve removing the file headers from working memory. Thus, at block 878, the personal key client deletes all the information associated with this password/passphrase change operation from its memory/storage (i.e., keys, password/passphrase, encrypted information).

Figure 19 illustrates operations for changing the public key of one or more "other users" for embodiments

of the present invention where the encryption key is encrypted with public key of the other user. The user or personal key client may be informed when the use changes its public key. For example a server may send a new certificate, containing the new public key, to the user or personal key client.

However the notification of a change in a public key occurs, the operations of **Figure 19** may be carried out when the public key of a use is to be changed from a current (i.e., old) public key *pki* to a "new public key" *pki_new*. As seen in **Figure 19**, the personal key client obtains a userid (*id*), current password/passphrase (*pw*), fileid(s) and new public key *pki_new* (block 1750). Such information may be obtained by the user providing some or all of the information to the personal key client and indicating that a public key update is to be performed. As described above, the files for which the public key update may be performed may be specified in any of the various ways described above.

The personal key client sends *id* and the user's credentials to the authentication server (block 1751) to request authentication of the user as an authorized user. As described above, the credentials may include a representation of the value of *pw* associated with the file (e.g., a hash value computed on *pw*) or a different password/passphrase (i.e., different from the value of *pw* specified block 1750).

Operations of the authentication server in response to receiving a request for authentication are seen in **Figure 6**. As described above, the authentication server provides a ticket to the personal key client in response to the authentication request

which is received by the personal key client (block 1753).

The personal key client sends an "access file headers" request along with the tuple defining the
userid and the fileids, for example, (id, *), and the
received ticket to the file server (block 1752).

Operations of the file server in response to the
"access file headers" request are illustrated in Figure
16. As described above, if the ticket verifies, the
file server sends the obtained file headers to the
personal key client (block 804) and the file server
waits for a response from the personal key client
(block 806). If the ticket does not verify, then the
rejected response is sent to the client (block 814).

Returning to **Figure 19**, the personal key client
receives the file header(s) from the file server (block
1754) and sends a "recover file encryption key" request
to the personal key server to recover the file
encryption keys for the file headers (block 1755) by
providing the tuple, for example, (id, *), and the
ticket from the authentication server. This operation
may be a "batch" operation where all encryption keys
are recovered and then processed or it may be performed
serially where a file encryption key is processed and
then another obtained. Thus, in response to the
request to recover file encryption keys the personal
key server carries out the operations as illustrated in
Figure 11. Accordingly, in response to the "recover
file encryption keys" request, the personal key server
compares the requestor's id (from the ticket) against
the id of the file owner in its stored access control
list. If the requestor's id is not found, then the
personal key server rejects the access request.
However, if the id is found, and it matches the id of

the file owner, then the personal key server extracts an encrypted value $\text{Enc}_{kc}(\text{Enc}_k(\text{ke}, \text{ki}, \text{Hash}(\text{ke}, \text{ki})))$ from each file header, decrypts it with its control key kc , and sends the decrypted values $\text{Enc}_k(\text{ke}, \text{ki}, \text{Hash}(\text{ke}, \text{ki}))$ back to the personal key client in the form of a tuple $(\text{fid}, \text{Enc}_k(\text{ke}, \text{ki}, \text{Hash}(\text{ke}, \text{ki})))$. Providing the decrypted $\text{Enc}_k(\text{ke}, \text{ki}, \text{Hash}(\text{ke}, \text{ki}))$ values with the fid values thus allows the personal key client to correctly associate each $\text{Enc}_k(\text{ke}, \text{ki}, \text{Hash}(\text{ke}, \text{ki}))$ value with its corresponding file header.

The personal key client receives the recovered keys (block 1757) and obtains a recovered encrypted key for processing (block 1756). The personal key client extracts the tuple (id, fid) from the file header (block 1758) and generates the key encrypting key k (block 1760). That is,

$$k = \text{Hash}(\text{id}, \text{pw}, \text{fid}).$$

The personal key client matches the fid and the encrypted value encrypted with k from the personal key server (block 1762), for example, $\text{Enc}_k(\text{ke}, \text{ki}, \text{Hash}(\text{ke}, \text{ki}))$, and decrypts the encrypted value with k (block 1762) to recover the encryption key(s), such as ke , ki and $\text{Hash}(\text{ke}, \text{ki})$. That is, $\text{ke}, \text{ki}, \text{Hash}(\text{ke}, \text{ki}) = \text{Dec}_k(\text{Enc}_k(\text{ke}, \text{ki}, \text{Hash}(\text{ke}, \text{ki})))$.

If a hash value is present in the encrypted value, the personal key client also computes $\text{Hash}(\text{ke}, \text{ki})$ using the decrypted ke, ki (block 1764) and compares the computed hash value with the decrypted $\text{Hash}(\text{ke}, \text{ki})$ to determine if they are equal (block 1766). If they are equal, then ke and ki are recovered correctly and they have not been changed. If they are not equal, then processing of the current header is concluded and, if more headers are available for processing (block 1774), a next header is obtained (block 1756) and

007280-62824960

processing begins again with block 1758. Such an error may also generate a message to a user so as to indicate that the password of the file associated with the file header was not changed and/or that an error occurred processing the header file.

The personal key client encrypts the key values, for example, ke , ki and $\text{Hash}(ke, ki)$, with pki_new (block 1770). That is,

$\text{Enc}_{pki_new}(ke, ki, \text{Hash}(ke, ki))$.

The personal key client replaces the current value of the encrypted keys for the user, such as $\text{Enc}_{pki}(ke, ki, \text{Hash}(ke, ki))$, in the file header with the new value $\text{Enc}_{pki_new}(ke, ki, \text{Hash}(ke, ki))$ (block 1772). At this point, the personal key client may continue processing additional file headers if any remain (block 1774).

If no more file headers remain (block 1774), the personal key client sends an "update file header" request or requests to the personal key server (block 1773) along with the updated file headers and the ticket.

Operations of the personal key server in response to the update file headers request are described above with reference to **Figure 17**. As described above, for each tuple $(fid, \text{Enc}_{pki_new}(ke, ki, \text{Hash}(ke, ki)))$ the personal key server encrypts $\text{Enc}_{pki_new}(ke, ki, \text{Hash}(ke, ki))$ with its control key kc to produce $\text{Enc}_{kc}(\text{Enc}_{pki_new}(ke, ki, \text{Hash}(ke, ki)))$, replaces the current value of $\text{Enc}_{kc}(\text{Enc}_{pki}(ke, ki, \text{Hash}(ke, ki)))$ in the file header with the new value $\text{Enc}_{kc}(\text{Enc}_{pki_new}(ke, ki, \text{Hash}(ke, ki)))$ and returns the updated file headers to the personal key client.

Returning to **Figure 19**, the personal key client receives the new file headers from the personal key server (block 1775). The personal key client sends a

"store updated file headers" request to the file server, along with the updated file headers and the ticket (block 1776). The personal key client then waits for a response from the file server (block 1778).

5 Operations of the file server are then carried out as described above with reference to **Figure 16**. If the replacement of file headers was successful, the file server sends a response message to the personal key client indicating that the file headers have been
10 replaced in the file server's database. When the personal key client receives the response from the file server, operations continue at block 1780 of **Figure 19**. The personal key client removes all unneeded copies of the file headers from its memory. As with the systems
15 described above, if the file headers are maintained locally, this may involve removing the file headers from working memory. Thus, at block 1780, the personal key client deletes all the information associated with this password/passphrase change operation from its
20 memory/storage (i.e., keys, password/passphrase, encrypted information).

 While the operations of Figures 15 through 19 are illustrated as being performed in a batch operation, such operations could also be performed on a header by
25 header basis. In such embodiments, the each header to be changed could be obtained, modified and then stored on the file server. Thus, the present invention should not be construed as limited to the particular
 operations illustrated in Figures 15 through 19.

30 As will be understood by those of skill in the art in light of the present disclosure, messages sent between the personal key client and the personal key server may be encrypted in session keys. This may ensure that the file encryption keys, which in some

cases might otherwise appear in the clear, are encrypted under a session key, thereby ensuring that the file encryption keys are protected on the communication path between the personal key client and the personal key server. If the network authentication mechanism is based on Kerberos, then the needed session encryption keys can be provided by Kerberos. However, any suitable mechanism for providing secure communications may be utilized in certain embodiments of the present invention.

In addition, cryptography could be used between the personal key client and the personal key server to protect the integrity of messages sent from one party to the other. In a like manner, cryptography could be used between the personal key client and the file server to protect the integrity, and possibly the secrecy, of messages sent from party to the other.

The flowcharts and block diagrams of **Figures 1** through **19** illustrate the architecture, functionality, and operation of possible implementations of systems, methods and computer program products for securing stored digital data. In this regard, each block in the flow charts or block diagrams represents a module, segment, or portion of code, which comprises one or more executable instructions for implementing the specified logical function(s). It should also be noted that in some alternative implementations, the functions noted in the blocks may occur out of the order noted in the figures. For example, two blocks shown in succession may in fact be executed substantially concurrently or the blocks may sometimes be executed in the reverse order, depending upon the functionality involved.

In the drawings and specification, there have been disclosed typical preferred embodiments of the

invention and, although specific terms are employed, they are used in a generic and descriptive sense only and not for purposes of limitation, the scope of the invention being set forth in the following claims.

09642879.082.100